

# RG-11 SATELLITE 75 Ohm Coaxial Cable Catalog #5916 Non-Plenum: CM(UL) c(UL) CMH

## CABLE CONSTRUCTION:

### CENTER CONDUCTOR:

14 AWG Copper/Steel  
 Nom. Dia: 0.0641"

### DIELECTRIC:


Foam Polyethylene  
 Diameter over Dielectric: 0.280" Nom.

### SHIELD:

Foil: 0.003" Aluminum Tape  
 Braid: 34 AWG Aluminum  
 60% Coverage  
 Nom. Diameter 0.311"

### JACKET:

FR-PVC  
 Diameter over Jacket: 0.405" +/- 0.010"  
 Nominal Jacket Thickness: 0.045"  
 Minimum Spot: 0.036"



## ELECTRICAL PROPERTIES:

SPARKER TEST: 2000 VAC  
 DIELECTRIC STRENGTH: Conductor to Shield: 4000 VDC  
 CAPACITANCE: 16.2 pF./Ft. Nom.  
 IMPEDANCE: 75.0 +/- 3.0 Ohms  
 VELOCITY OF PROPAGATION: 82.0% Nom.  
 DCR: Conductor: 11.0 Ohms/1000 Ft. Nom.  
 SRL: 20 dB (5 - 1000 MHz) 100% Swept Tested  
 15dB (1000 - 2200 MHz)

## MECHANICAL PROPERTIES:

MINIMUM BEND RADIUS:  
 Loaded: 20 Times Cable OD  
 Unloaded: 10 Times Cable OD  
 CABLE TEMP. RATING:  
 Temp: 75°C

## ATTENUATION:

dB/100 FT. (NOM.)	@ FREQUENCY MHz
0.17 dB	1 MHz
0.45 dB	10 MHz
0.89 dB	50 MHz
1.21 dB	100 MHz
1.68 dB	200 MHz
2.37 dB	400 MHz
3.27 dB	700 MHz
3.77 dB	900 MHz
3.95 dB	1000 MHz
4.35 dB	1200 MHz
4.75 dB	1450 MHz
5.25 dB	1800 MHz
5.75 dB	2200 MHz